Data Sheet
Fujitsu PRIMERGY TX100 S3p Server

Enter the world of PRIMERGY TX servers

PRIMERGY TX tower servers are ideal for use in SMEs or branch offices. They increase operational efficiency by providing rock solid, record-breaking, energy efficient performance. That performance is built on 20-years of pioneering work in Green IT. As a customer, you benefit from a reduction in your organization's environmental impact and lower running costs. The reliability is proven by testing the machines through 5000 boot cycles – far more than other vendors do. PRIMERGY TX servers are also easy to manage via the PRIMERGY ServerView Suite, reducing IT admin workload and costs. Plus, tower to rack conversion kits are available for most TX systems, ensuring investment protection.

PRIMERGY TX100 S3p

The PRIMERGY TX100 S3p is ideal for SMEs, looking for a first server with Intel® Xeon® support. With a maximum of 32 GB of RAM, and excellent processor performance, it offers more than enough performance for all classic server tasks, such as file, print, web or office applications. The dual onboard gigabit LAN, makes it easier to do business 24x7. Moreover, the TX100 S3p is incredibly silent making it an excellent choice for any office environment. With its optional 0-Watt functionality and a choice of two highly efficient power supply units, the TX100 S3p minimizes costs and the environmental impact.

Features and Benefits

Main Features	Benefits
■ An excellent first server for SMEs looking for Intel® Xeon® support and up to 32 GB of RAM	■ Great price-performance ratio - ideal for all classic server tasks like file, print, web or office applications
■ Choose between a power supply unit (PSU) with 85% efficiency or with 94% energy efficiency and 0-Watt functionality	■ Benefit from Fujitsu's pioneering experience in Green IT - save money and minimize the environmental impact
■ Effective air flow design for low noise levels	■ Silent system for an ergonomic working environment
■ Dual onboard gigabit LAN, ECC memory and optional SATA RAID 5/6 with FBU	■ Keep business processes going - 24x7
■ Halogen-free printed circuit board	■ For environmentally friendly waste disposal

Technical details

PRIMERGY TX100 S3p		
Housing types	Tower	Tower
Storage drive architecture	4x 3.5-inch SATA	4x 3.5-inch SATA
Power supply	Standard	Standard (0-Watt)
Mainboard		
Mainboard type	D 3009	
Chipset	Intel® C200	
Processor quantity and type	1 x Intel® Celeron® processor / Intel® Pentium® processor / Intel® Core™ i3 processor / Intel® Xeon® processor E3 series	
Processor	Intel® Celeron® processor G550 (2C/2T, 2.60 GHz, TLC: 2 MB, Turbo: No, 1066 MHz, 65 W)	
	Intel® Pentium® processor G640 (2C/2T, 2.80 GHz, TLC: 3 MB, Turbo: No, 1066 MHz, 65 W)	
	Intel® Xeon® processor E3-1220v2 (4C/4T, 3.10 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 69 W)	
	Intel® Xeon® processor E3-1230v2 (4C/8T, 3.30 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 69 W)	
	Intel® Xeon® processor E3-1240v2 (4C/8T, 3.40 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 69 W)	
Memory slots	4	
Memory slot type	DIMM (DDR3)	
Memory capacity (min. - max.)	2 GB - 32 GB	
Memory protection	ECC	
Memory options	2 GB (1 module(s) 2 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM	
	4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM	
	8 GB (1 module(s) 8 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM	
Memory modules notes	Only UDIMM (unbuffered) supported	
Interfaces		
USB ports	9 (2x front, 6x rear, 1x internal for backup device)	
Graphics (15-pin)	1 x VGA (ATI ES1000 (64MB) on board)	
Serial 1 (9-pin)	1 x RS232	
LAN / Ethernet (RJ-45)	2 x Gbit/s Ethernet	
Status LEDs	Power (green)	
I/O controller on board		
Serial ATA total	6	
RAID controller	4 port SATA with RAID 0/1/10 for HDDs	
SATA Controller	Intel® C200	
LAN Controller	Intel® 82574L + Intel® 82579LM onboard, 2 x 10/100/1000 Mbit/s Ethernet, PXE-Boot by LAN via PXE-Server, Teaming supported	
Trusted Platform Module (TPM)	Infineon / 1.2 (option)	
Slots		
PCI-Express 3.0 x8	1 x	
PCI-Express 3.0 x8 (mech. x16)	1 x	
PCI-Express 2.0 x1 (mech. x4)	1 x notched for x16 cards	
PCI-Express 2.0 x4	1 x notched for x16 cards	
Slot Notes	In configurations with Intel® Core™ i3 or Intel® Pentium® processors slots are operated with PCI-Express 2.0.	
Storage drive bay configuration	4x 3.5" easy change SATA	
Notes accessible drives	2 (1 bay is occupied by DVD/DVD-RW, 3.5-inch)	

General software information	
Fan configuration	Silent system fans
Fan notes	Non hot-plug
Operating panel	
Operating buttons	On/off switch
Status LEDs	Power (green)
Operating Systems and Virtualization Software	
Certified or supported operating systems and virtualization software	Microsoft® Hyper-V™ Server 2008 R2 Microsoft® Windows Server® 2008 R2 Datacenter Microsoft® Windows Server® 2008 R2 Enterprise Microsoft® Windows Server® 2008 R2 Standard Microsoft® Windows Server® 2008 R2 Foundation Microsoft® Windows® Web Server 2008 R2 Microsoft® Windows® Small Business Server Essentials 2011 Microsoft® Windows® Small Business Server 2011 Premium Add-On Microsoft® Windows® Small Business Server Standard 2011 Microsoft® Windows® Server 2008 Enterprise Microsoft® Windows® Server 2008 Standard Novell® SUSE Linux Enterprise Server 11 Novell® SUSE Linux Enterprise Server 10 Red Hat® Enterprise Linux 6 Red Hat® Enterprise Linux 5
Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473
Operating system notes	Support of other Linux derivatives on demand Red Hat® certification starting with version 5.8 / 6.4.
Server Management	
Standard	ServerView Suite - Deploy SV Installation Manager
Option	ServerView Suite - Deploy SV Deployment Manager (full version) ServerView Suite - Integrate SV Integration pack for Fujitsu ManageNow® solution
Server Management notes	Regarding Operating System dependencies and product details for ServerView Suite Software Products see dedicated Product Data sheets.
Dimensions / Weight	
Floor-stand (W x D x H)	175 x 419 x 395 mm
Weight	up to 14 kg
Environmental	
Operating ambient temperature	10 - 35°C
Operating temperature note	ETSI 300 019-2-3 Class 3.1
Operating environment	FTS 04230 – Guideline for Data Center (installation locations)
Operating environment Link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe
Noise emission	According to ISO9296
Sound pressure (LpAm)	25 dB(A) (idle)/ 25 dB(A) (operating)
Sound power (LWAd; 1B = 10dB)	3.9B (idle)/ 3.9B (operating)
Noise notes / description	Noise emissions and operation modes depend on system configuration.
Electrical values	
Power supply configuration	1
Standard power supply output	250 W
Rated voltage range	100 V - 127 V / 200 V - 240 V
Rated frequency range	47 Hz - 63 Hz
Rated current max.	100 V – 240 V / 5.0 – 2.5 A

Electrical values	
Rated current in basic configuration	100 V – 240 V / 1,5 – 0,6 A
Active power (min. configuration)	22 W
Active power (max. configuration)	209 W
Apparent power (max. configuration)	211 VA
Heat emission	752.4 kJ/h (713.1 BTU/h)
Power Supply Notes	Fujitsu patented 0-Watt standby technology (optional).

Compliance	
Germany	GS (planned)
Europe	CE Class A *
USA/Canada	CSA us ULc/us FCC Class A
Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronical equipment)
Japan	VCCI Class A
South Korea	KC (planned)
China	CCC (planned)
Australia/New Zealand	C-Tick (AS / NZS CISPR 22 Class A)
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.
Compliance link	http://sp.ts.fujitsu.com/sites/certificates/

Components

Storage disks	HDD SATA, 6 Gb/s, 500 GB, 7200 rpm, non hot plug, 3.5-inch, economic
	HDD SATA, 6 Gb/s, 500 GB, 7200 rpm, non hot plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 250 GB, 7200 rpm, non hot plug, 3.5-inch, economic
	HDD SATA, 6 Gb/s, 3 TB, 7200 rpm, non hot plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 2 TB, 7200 rpm, non hot plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7200 rpm, non hot plug, 3.5-inch, business critical
Backup Drives	DDS Gen5, 36 GB, 3 MB/s, half height, USB 2.0
	DDS Gen6, 80 GB, 6 MB/s, half height, USB 2.0
	RDX Drive, 160 GB, 320 GB, 500 GB, 1 TB , 25 MB/s, half height, USB 2.0
Optical drives	Blu-ray Disc™ Triple Writer, (6x BD-ROM ; 8x DVD; 24x CD), slimline, SATA I
	DVD-ROM, (16xDVD; 48xCD), half height, SATA I
	DVD Super Multi, (16xDVD, 8xDVD+RW 6xDVD-RW, 12xDVD-RAM; 48xCD, 32xCD-RW), half height, SATA I
RAID Controller	RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 5/6 512MB (D2616), 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU (based on LSI SAS2108)
LAN Controller	Ethernet Ctrl. 1 x 1 Gbit/s Intel® Gigabit CT Desktop Adapter
	Ethernet Ctrl. 2 x 1 Gbit/s Fujitsu LAN Adapter D2735-2
Graphics add on cards	NVIDIA® Quadro® NVS 300, PCIe x1, 2x DVI/VGA

Warranty	
Standard Warranty	1 year

Warranty	
Service level	On-site Service (depending on country)
Maintenance and Support Services - the perfect extension	
Recommended Service	7x24, Onsite Response Time: 4h.
Service Lifecycle	5 years
Service Weblink	http://www.fujitsu.com/fts/services

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu PRIMERGY TX100 S3p, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio
Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products
www.fujitsu.com/global/services/computing/

Software
www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY TX100 S3p, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.
Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.
Please find further information at http://www.fujitsu.com/global/about/environment/

Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact
FUJITSU LIMITED

Website: www.fujitsu.com
2012-08-06 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html
Copyright © Fujitsu Technology Solutions

Data Sheet
Fujitsu PRIMERGY TX100 S3 Server

Enter the world of PRIMERGY TX servers

PRIMERGY TX tower servers are ideal for use in SMEs or branch offices. They increase operational efficiency by providing rock solid, record-breaking, energy efficient performance. That performance is built on 20-years of pioneering work in Green IT. As a customer, you benefit from a reduction in your organization's environmental impact and lower running costs. The reliability is proven by testing the machines through 5000 boot cycles – far more than other vendors do. PRIMERGY TX servers are also easy to manage via the PRIMERGY ServerView Suite, reducing IT admin workload and costs. Plus, tower to rack conversion kits are available for most TX systems, ensuring investment protection.

PRIMERGY TX100 S3

The PRIMERGY TX100 S3 is ideal for SMEs, looking for a first server with Intel® Xeon® support.With a maximum of 32 GB of RAM, and excellent processor performance, it offers more than enough performance for all classic server tasks, such as file, print, web or office applications. The dual onboard gigabit LAN, makes it easier to do business 24x7. Moreover, the TX100 S3 is incredibly silent making it an excellent choice for any office environment. With its optional zero Watt functionality and a choice of two highly efficient power supply units, the TX100 S3 minimizes costs and the environmental impact.

Features and Benefits

Main Features	Benefits
■ An excellent first server for SMEs looking for Intel® Xeon® support and up to 32 GB of RAM	■ Great price-performance ratio - ideal for all classic server tasks like file, print, web or office applications
■ Choose between a power supply unit (PSU) with 85% efficiency or with 94% energy efficiency and 0-Watt functionality	■ Benefit from Fujitsu's pioneering experience in Green IT - save money and minimize the environmental impact
■ Low noise levels	■ Effective air flow design ensures a silent system for an ergonomic working environment.
■ Dual onboard gigabit LAN, ECC memory and optional SATA RAID 5/6 with BBU	■ Keep business processes going - 24x7
■ Halogen-free printed circuit board	■ For environmentally friendly waste disposal

Technical details

PRIMERGY TX100 S3		
Housing types	Tower	Tower
Storage drive architecture	4x 3.5-inch SATA	4x 3.5-inch SATA
Power supply	Standard	Standard (0-Watt)
Mainboard		
Mainboard type	D 3009	
Chipset	Intel® C200	
Processor quantity and type	1 x Intel® Core™ i3 processor / Intel® Pentium® processor / Intel® Xeon® processor E3 series	
Processor	Intel® Core™ i3-2100 processor (2C/4T, 3.10 GHz, TLC: 3 MB, Turbo: No, 1333 MHz, 65 W)	
	Intel® Core™ i3-2120 processor (2C/4T, 3.30 GHz, TLC: 3 MB, Turbo: No, 1333 MHz, 65 W)	
	Intel® Pentium® processor G620 (2C/2T, 2.60 GHz, TLC: 3 MB, Turbo: No, 1066 MHz, 65 W)	
	Intel® Xeon® processor E3-1220 (4C/4T, 3.10 GHz, TLC: 8 MB, Turbo: 3.40 GHz, 1333 MHz, 80 W)	
	Intel® Xeon® processor E3-1230 (4C/8T, 3.20 GHz, TLC: 8 MB, Turbo: 3.60 GHz, 1333 MHz, 80 W)	
	Intel® Xeon® processor E3-1240 (4C/8T, 3.30 GHz, TLC: 8 MB, Turbo: 3.70 GHz, 1333 MHz, 80 W)	
Memory slots	4	
Memory slot type	DIMM (DDR3)	
Memory capacity (min. - max.)	2 GB - 32 GB	
Memory protection	ECC	
Memory options	2 GB (1 module(s) 2 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM	
	4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM	
	8 GB (1 module(s) 8 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM	
Memory modules notes	Only UDIMM (unbuffered) supported	
Interfaces		
USB ports	9 (2x front, 6x rear, 1x internal for backup device)	
Graphics (15-pin)	1 x VGA (ATI ES1000 (64MB) on board)	
Serial 1 (9-pin)	1 x RS232	
LAN / Ethernet (RJ-45)	2 x Gbit/s Ethernet	
Status LEDs	Power (green)	
I/O controller on board		
Serial ATA total	6	
RAID controller	4 port SATA with RAID 0/1/10 for HDDs	
SATA Controller	Intel® C200	
LAN Controller	Intel® 82574L + Intel® 82579LM onboard, 2 x 10/100/1000 Mbit/s Ethernet, PXE-Boot by LAN via PXE-Server, Teaming supported	
Trusted Platform Module (TPM)	Infineon / 1.2 (option)	
Slots		
PCI-Express 2.0 x1 (mech. x4)	1 x notched for x16 cards	
PCI-Express 2.0 x4	1 x notched for x16 cards	
PCI-Express 2.0 x8 (mech. x16)	1 x	
PCI-Express 2.0 x8	1 x	
Storage drive bay configuration	4x 3.5" easy change SATA	

Notes accessible drives	2 (1 bay is occupied by DVD/DVD-RW, 3.5-inch)
General software information	
Fan configuration	Silent system fans
Fan notes	Non hot-plug
Operating panel	
Operating buttons	On/off switch
Status LEDs	Power (green)
Operating Systems and Virtualization Software	
Certified or supported operating systems and virtualization software	Microsoft® Hyper-V™ Server 2008 R2 Microsoft® Windows Server® 2008 R2 Datacenter Microsoft® Windows Server® 2008 R2 Enterprise Microsoft® Windows Server® 2008 R2 Standard Microsoft® Windows Server® 2008 R2 Foundation Microsoft® Windows® Web Server 2008 R2 Microsoft® Windows® Small Business Server Essentials 2011 Microsoft® Windows® Small Business Server 2011 Premium Add-On Microsoft® Windows® Small Business Server Standard 2011 Microsoft® Windows® Server 2008 Enterprise Microsoft® Windows® Server 2008 Standard Novell® SUSE Linux Enterprise Server 11 Novell® SUSE Linux Enterprise Server 10 Red Hat® Enterprise Linux 6 Red Hat® Enterprise Linux 5
Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473
Operating system notes	Support of other Linux derivatives on demand
Server Management	
Standard	ServerView Suite - Deploy SV Installation Manager
Option	ServerView Suite - Deploy SV Deployment Manager (full version) ServerView Suite - Integrate SV Integration pack for Fujitsu ManageNow® solution
Server Management notes	Regarding Operating System dependencies and product details for ServerView Suite Software Products see dedicated Product Data sheets.
Dimensions / Weight	
Floor-stand (W x D x H)	175 x 419 x 395 mm
Weight	up to 14 kg
Environmental	
Operating ambient temperature	10 - 35°C
Operating temperature note	ETSI 300 019-2-3 Class 3.1
Operating environment	FTS 04230 – Guideline for Data Center (installation locations)
Operating environment Link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe
Noise emission	According to ISO9296
Sound pressure (LpAm)	25 dB(A) (idle)/ 25 dB(A) (operating)
Sound power (LWAd; 1B = 10dB)	3.9B (idle)/ 3.9B (operating)
Noise notes / description	Noise values may vary according to configuration
Electrical values	
Power supply configuration	1
Standard power supply output	250 W
Rated voltage range	100 V - 127 V / 200 V - 240 V
Rated frequency range	47 Hz - 63 Hz
Rated current max.	100 V – 240 V / 5.0 – 2.5 A

Electrical values	
Rated current in basic configuration	100 V – 240 V / 1,5 – 0,6 A
Active power (min. configuration)	22 W
Active power (max. configuration)	209 W
Apparent power (max. configuration)	211 VA
Heat emission	752.4 kJ/h (713.1 BTU/h)
Power Supply Notes	Fujitsu patented 0-Watt standby technology (optional).

Compliance	
Germany	GS (planned)
Europe	CE Class A *
USA/Canada	CSA us ULc/us FCC Class A
Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronical equipment)
Japan	VCCI Class A
Australia/New Zealand	C-Tick (AS / NZS CISPR 22 Class A)
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.
Compliance link	http://sp.ts.fujitsu.com/sites/certificates/

Components

Storage disks	HDD SATA, 3 Gb/s, 2000 GB, 7200 rpm, non hot plug, 3.5-inch, business critical
	HDD SATA, 3 Gb/s, 1000 GB, 7200 rpm, non hot plug, 3.5-inch, business critical
	HDD SATA, 3 Gb/s, 500 GB, 7200 rpm, non hot plug, 3.5-inch, business critical
	HDD SATA, 3 Gb/s, 250 GB, 7200 rpm, non hot plug, 3.5-inch, economic
Backup Drives	DDS Gen5, 36 GB, 3 MB/s, half height, USB 2.0
	DDS Gen6, 80 GB, 6 MB/s, half height, USB 2.0
	RDX Drive, 160 GB, 320 GB, 500 GB, 1 TB , 25 MB/s, half height, USB 2.0
Optical drives	Blu-ray Disc™ Triple Writer, (4x BD-RW; 16x DVD; 40x CD), half height, SATA I
	DVD-ROM, (16xDVD; 48xCD), half height, SATA I
	DVD Super Multi, (16xDVD, 8xDVD+RW 6xDVD-RW, 12xDVD-RAM; 48xCD, 32xCD-RW), half height, SATA I
RAID Controller	RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 5/6 512MB (D2616), 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU (based on LSI SAS2108)
LAN Controller	Ethernet Ctrl. 1 x 1 Gbit/s Intel® Gigabit CT Desktop Adapter
	Ethernet Ctrl. 2 x 1 Gbit/s Fujitsu LAN Adapter D2735-2
Graphics add on cards	NVIDIA® Quadro® NVS 300, PCIe x1, 2x DVI/VGA

Warranty	
Standard Warranty	1 year
Service level	On-site Service (depending on country)
Maintenance and Support Services - the perfect extension	
Recommended Service	7x24, Onsite Response Time: 4h.
Service Lifecycle	5 years
Service Weblink	http://www.fujitsu.com/fts/services

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu PRIMERGY TX100 S3, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio
Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products
www.fujitsu.com/global/services/computing/

Software
www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY TX100 S3, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.
Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.
Please find further information at http://www.fujitsu.com/global/about/environment/

Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact
FUJITSU LIMITED

Website: www.fujitsu.com
2012-08-06 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html
Copyright © Fujitsu Technology Solutions